

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen

Intyg
Certificate

REC'D 04 FEB 2003

WIPO

PCT

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Idevio AB, Göteborg SE
Applicant (s)

(21) Patentansökningsnummer 0200167-5
Patent application number

(86) Ingivningsdatum 2002-01-21
Date of filing

Stockholm, 2003-01-22

För Patent- och registreringsverket
For the Patent- and Registration Office

Sonia André
Sonia André

Avgift
Fee

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

AWAPATENT AB

Kontor/Handläggare

Göteborg/Henrik Olsson/HON

JOHAN PERSSON

Ansökningsnr

Vår referens

SE-2026029

1

DEVICE AND CARRIER FOR PROVIDING MAP INFORMATION DATA

Ink. t. Patent- och registerverket

2002-01-21

Huvudfaxen Kasson

5 Technical field of invention

One aspect of the present invention relates to a device for providing map information data interactively to a display unit operated by a user.

10

Another aspect of the present invention relates to a map information data carrier to be used in a device for providing map information data.

15 Yet another aspect of the present invention relates to a device for providing map information data to a planning apparatus for planning at least one of locations of society facility and travel routes.

20

Background of invention

Digital maps are now finding their way to the public. We see them at many sites at Internet, in PC atlases, in

25 handheld navigators, for instance of the GPS type, and in many other devices. Most data is geographically related and can therefore be presented at a map.

Digital map data is either in raster or vector form.

30 Raster maps are easy to use in applications since they

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfaxen Kassar

2

have a uniform data structure where each pixel represents a color or a natural feature class but they have many disadvantages compared to vector maps. The most obvious one is that they do not scale well since images turn
5 blocky when zoomed. They also cannot contain extra information on features in the image. Vector maps on the other hand are more complex to use but offer more flexibility and contain more information.

10 Geographic databases can be very large and slow to access. Many geographic databases take several gigabyte of storage. Because of their complexity and size these databases are not used to the extent that they may deserve.

15

Preparation of data for a map application is a costly process. The most common technique today is to prepare one database for each presentation scale that the application uses. This makes it possible to see an
20 overview of a large area without reading most of the database. The downside is of course that it is expensive and complex to handle several databases instead of one. Ideally one database would be efficient enough for the whole scale range that the application uses.

25

Summary of invention

Automatic map information data generalization, or
30 aggregation, is a promising ongoing field of research where the result is a number of resolution levels, each in a certain scale. The generalization process consists among other things of selecting the features that are

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfaxen Kasson

3

suitable for a certain scale (or resolution level), simplifying geometry of features and replacing some features with a different representation.

- 5 Automatic map information data generalization leads to databases presenting resolutions at a plurality of levels. A multi-resolution database, which is one of the central parts of the present invention, has the ability to return data in the resolution that the user requests.
- 10 Not only should such a database be more efficient when requesting low resolution data than if requesting the original resolution, it should also be able to return a representation that is more suitable for the scale. One example is that cities could be represented by points at
- 15 low resolutions and with polygons at high resolutions.

- One aspect of the present invention relates to a device for providing map information data interactively to a display unit operated by a user. Key hardware elements of
- 20 the device include a processor and a memory comprising a map information database, or the multi-resolution database. The map information database comprises map information data representing geographical features. The map information data is based on aggregations of at least
- 25 one of nodes, links and rings, each one of which corresponding to geographic features.

- The structure of the node-link-ring approach is the following. A node can be seen as a point, or coordinate,
- 30 related to at least one geographical feature. A link can be seen a line, even though the present invention also encompasses more advanced geometrical arrangements such as arcs, having nodes in each of its end points. A ring

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfaxen Kassar

4

should be interpreted as a circular arrangement or a polygonal arrangement. Also the arrangements also have to be closed. A ring is constituted by a plurality of links. Thus the internal structure of the approach is that the

5 most basic component of the approach is the node, followed by a link followed by a ring. Data, such as points, starting points, ring points, i.e. concerning the three components are stored. Also, attributes to a node, a link, or a ring are possible. Also it is possible that

10 attributes are defined in higher level objects related to rings, links and nodes. An attribute can be seen as a descriptor in relation to a for instance a point. An attribute can comprise a name, a distance between two points, altitude.

15

Combined with additional data, nodes, links and rings comprise all the necessary information that is needed to increase the resolution of the map information. What nodes, links and rings that will be provided by the

20 device depend on the level of aggregation that corresponds to a resolution level. Thus, aggregations offer a number of resolution levels, where the map information data of a higher resolution level comprises additional map information data, resulting in

25 more detailed map information presented on the display unit, compared to the map information data of a lower resolution level. The map information data of a higher resolution level is generated by enhancement of the map information data of a lower resolution level combined

30 with the additional data, the enhancement being based on disaggregation of at least one of the nodes, links and rings. The processor being configured for:

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfoxen Kassan

5

-receiving from the user a request for map information data;

5 -providing to the display unit, in the case of the request being a first request, map information data at a predetermined resolution level and, in the case of the request being subsequent request, map information data at a higher resolution level. It should be pointed out that disaggregation also includes line resolution enhancement.

10 A key advantage of the present invention is that it makes multiple databases for different scales obsolete. Other advantages include a higher speed in the communication of map information data due to that less map information data is communicated as compared to prior art map
15 information data communication techniques. Another advantage is a reduction of the cost for preparation and communication of map information. It also leads to a decreased need of storage space since the map information data requires less storage space.

20

According to one preferred embodiment the predetermined resolution level corresponds to the lowest resolution level. This offers the opportunity of allowing a user to start the use of the device at a level having the lowest
25 resolution.

According to another embodiment the processor is further configured for, in the case of the request being subsequent request, providing map information data at a
30 lower resolution level. This offers the opportunity of allowing a user to go back, i.e. to receive map information data of a level of lower resolution.

Ink. t. Patent- och reg.verket

+46 31630263

2002 -01- 2 1

Huvudfoxen Kassan

6

According to another embodiment, in the case of the request being subsequent request, the difference in resolution level between a presently provided map information data and a previously provided map information data is 1, or greater than 1. This offers the opportunity of a user not to obtain map information data relating to a resolution level of which the user has no interest, i.e. it makes it possible to "jump over" one or more resolution levels. However, the device is arranged to disaggregate the nodes, links, and rings at each level in order to provide the map information data to be provided to the display unit.

In another embodiment the device further comprises communication means in order to communicate map information data to a more distant location. In such an embodiment the memory comprising the map information database is remotely located and accessible using the communication means. This offers the advantage of having easier updating of the map information of a map information company.

In another embodiment the database is arranged in memories at two locations, in which lower resolution levels are arranged in one memory and higher resolution levels are arranged in the other. This offers the exemplary advantage of user's to have a specific map information data as a starting point in the user's use process. As the map information data becomes more specific the required map information data is provided from a second device comprising a second memory comprising the map information database including higher resolution levels.

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassar

7

In another embodiment the display unit is constituted by a computer screen, i.e. the device and display unit is incorporated in the concept called personal computer.

5

In other embodiments the device further comprises means for communication between the device and the display unit and the display unit is constituted by one of a cell phone, personal digital assistant (PDA), and a navigator.

10 These applications include providing map information data to a mobile setting. One present type of navigator is a GPS navigator. Another type of setting is the providing of map information data using a data communication network, such as the internet, to user. This includes the
15 term internet maps.

Another aspect of the present invention is a carrier, such as a CD-ROM (CD ROM) or a portable drive, comprising the map information database, i.e. a map information data
20 carrier to be used in a device for providing map information data, comprising a map information database comprising map information data representing geographical features. The map information data is based on
25 aggregations of at least one of nodes, links and rings, each one of which corresponding to geographic features, offering a number of resolution levels. The map information data of a higher resolution level comprises additional map information data, resulting in more detailed map information presented on the display unit,
30 compared to the map information data of a lower resolution level. The map information data of a higher resolution level being generated by enhancement of the map information data of a lower resolution level combined

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfoxen Kassan

8

with the additional data, the enhancement being based on disaggregation of at least one of the nodes, links and rings. This aspect is highly relevant in the context of so called a CD-Atlas (or CD Atlas). By using the carrier in relation to a computer the map information database is easily available. This aspect is closely related to the first aspect is therefore not described further here.

Yet, another aspect of the present invention deals with a device for providing map information data to a planning apparatus for planning at least one of locations of society facility and travel routes. The device comprises the same hardware components as the first device presented above. However, a chief difference is that the device is not arranged to provide the map information data to a display unit, but rather a planning apparatus. The structure of the map information database is the same, i.e. the map information data is based on aggregations of at least one of nodes, links and rings, each one of which corresponding to geographic features. Therefore the description is limited in these respects. The processor is configured for:

- receiving from the user a request for map information data;
- providing to the planning apparatus, in the case of the request being a first request, map information data at a predetermined resolution level and, in the case of the request being subsequent request, map information data at a higher resolution level.

A key advantage of this aspect is that it makes facilitates an easy and reliable way of providing map information data to a planning apparatus. For instance

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassan

9

the device according to this aspect can be an important tool in terms of planning of locations of society facility, such as where to locate super markets, hospitals, and the like. Also it can be used to plan roads stretches and the like. Another important use of the device according to this aspect is the planning of travel routes since the attributes of the node-link-ring approach can comprise distance data between two points in the geographical dimension.

10

The database using the node-link-ring approach is developed in the following way.

1. Read original geographic vector data for a region and clip it to that region.
2. Create a set of data with lower resolution and store it.
3. Create supplemental data so that these together with the lower resolution data can recreate the original data and store it separately.
4. Repeat the process from step 1 for all regions comprised in the database.
5. Read one or more adjacent regions at resolution R and separate in a lower resolution and in supplemental data for recreation of resolution R. Store the supplemental for each of the read regions. Join the clipped objects at the borders and store the low-resolution data in the database.
6. Repeat step 5 for all regions at the current resolution in the database.
7. Repeat from step 5 with a lower resolution until the lowest required resolution is reached.

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassan

10

Lexical section

The term cell phone is here considered to include cell
phone, cellphone, cellular phone, mobile telephone and
5 mobile phone.

The term geographical (geography) is here considered to
include topographical (topography), topological
(topology) and demographical (demography).

10

The term map information data is here considered to
include river, lake, sea, city, part of city, such as a
suburb, building, house, road, street, railroad, canal,
forest, area under cultivation, mountain, and altitude
15 indicator.

Also included in the term map information data are the
contents of the attributes that convey information to the
map information data. Types of attributes include name,
20 symbols, such as flags, distance e.g. between nodes, map
line features, such as thickness and structure (e.g.
dashed line), population, and different types of forests.

25

Brief description of the drawings

The disclosure of the present invention is supported by
use of the following drawings.

30

Figure 1 schematically presents an embodiment of a device
for providing map information data interactively to a
display unit operated by a user.

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kasson

11

Figure 2 schematically presents a node, a link and a ring.

Figure 3 schematically presents another embodiment of a device for providing map information data interactively to a display unit operated by a user.

Figure 4 schematically presents another embodiment of a device for providing map information data interactively to a display unit operated by a user.

Figure 5 schematically presents yet another embodiment of a device for providing map information data to a planning apparatus for planning at least one of locations of society facility and travel routes is disclosed.

Figures 6A, 6B, 6C and 6D schematically present a map comprised in the database at different resolution levels.

20

Description of preferred embodiments

In Figure 1, a device 1 for providing map information data 3 interactively to a display unit 5 operated by a user is presented. The device 1 comprises a processor 7 and a memory 9 comprising a map information database 11. The map information database 11 comprises map information data 3 representing geographical features. The map information data 3 is based on aggregations of at least one of nodes 15, links 17 and rings 19, each one of which corresponding to geographic features. The structure of the node 15, links 17 and rings 19 offer a number of

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfoxen Kassar

12

resolution levels. In Figure 2, examples of a node 15, a link 17, and a ring 19 are presented. As can be seen in Figure 2, a ring 19 consists of a number of related links 17 and nodes 15, and a link 17 consists of two connected
5 nodes 15.

In one preferred embodiment, there are attributes, as described above, associated with the nodes 15, links 17 and rings 19.

10

The map information data 3 of a higher resolution level comprises additional map information data, resulting in more detailed map information data 3 presented on the display unit 5, compared to the map information data 3 of
15 a lower resolution level.

The map information data 3 of a higher resolution level is generated by enhancement of the map information data 3 of a lower resolution level combined with additional
20 data. The enhancement is based on disaggregation of at least one of the nodes 15, links 17, and rings 19.

The processor 7 is configured for:

- receiving from the user a request for map information
25 data 3;
- providing to the display unit 5, in the case of the request being a first request, map information data 3 at a predetermined resolution level and, in the case of the request being subsequent request, map information data 3
30 at a higher resolution level.

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassan

13

In a preferred embodiment the predetermined resolution level corresponds to the lowest resolution level being a geodata level.

- 5 In a preferred embodiment the processor 7 is further configured for, in the case of the request being subsequent request, providing map information data 3 at a lower resolution level.
- 10 On a preferred embodiment, in the case of the request being subsequent request, the difference in resolution level between a presently provided map information data 3 and a previously provided map information data 3 is 1, or greater than 1. This leads to the possibility of the user
- 15 to obtain map information data 3 at a desired level without having to wait for the communication of the map information data 3 related to resolution levels that the user is not interested to obtain. However, the processor 7 disaggregates the map information of the intermediate
- 20 resolution levels but they are not provided to the display unit 5.

- In a preferred embodiment presented in Figure 3, the device further 1 comprises communication means 23 and
- 25 wherein the memory 9 comprising the map information database 11 is remotely located and accessible using the communication means 23. In this embodiment the communication means 23 is constituted by a data communication network.

30

In a preferred embodiment, the database 11 of the device 1 is arranged in memories 9 at two locations, in which lower resolution levels are arranged in one memory 9 and

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfoxen Kossan

14

higher resolution levels are arranged in the other memory
9. This is presented in Figure 4.

In a preferred embodiment the display unit 5 is
5 constituted by a computer screen.

In other preferred embodiments of the device 1 comprising
means for communication 23 between the device 1 and the
display unit 5, where the display unit 5 is constituted
10 by one of a cell phone, personal digital assistant (PDA),
and a navigator, i.e. the device 1 is technically
applicable in a cell phone, personal digital assistant
(PDA), and a navigator.

15 In one embodiment a map information data carrier to be
used in relation to a device 1 for providing map
information data 3 is hereby disclosed. It comprises the
map information database 11 comprising map information
data 3 as has been described above. Due to the
20 similarities with the description above, this will not be
described again.

In another preferred embodiment a device 31 is disclosed,
for providing map information data 3 to a planning
25 apparatus 33 for planning at least one of locations of
society facility and travel routes. The device 31
comprises a processor 7 and a memory 9 comprising a map
information database 11. The map information database 11
comprises map information data 3 representing
30 geographical features. The map information data 3 is
based on aggregations of at least one of nodes 15, links
17 and rings 19, each one of which corresponding to
geographic features, offering a number of resolution

Ink. t. Patent- och reg.verket

7007 -01- 2 1

Huvudfoxen Kesson

15

levels. The map information data 3 of a higher resolution level comprises additional map information data 3, resulting in more detailed map information, compared to the map information data 3 of a lower resolution level.

5 The map information data 3 of a higher resolution level is generated by enhancement of the map information data 3 of a lower resolution level combined with the additional data. The enhancement is based on disaggregation of at least one of the nodes 15, links 17 and rings 19. The

10 device 31 also comprises communication means 35 for communicating the map information data 3 to the planning apparatus 33. In this embodiment the communication means 35 is constituted by one of a data communication network, such as the internet, and a floppy disk stations-floppy

15 disk arrangement.

The processor 7 is configured for:

- receiving from the user a request for map information data 3;
- 20 -providing to the planning apparatus 33, in the case of the request being a first request, map information data 3 at a predetermined resolution level and, in the case of the request being subsequent request, map information data 3 at a higher resolution level.

25

Now turning to the map information data 3 at the different resolution levels as it is used by the device 1 and the device 31, a simple example of the disaggreagation of map information data 3 covering four

30 resolution levels is presented in Figures 6A, 6B, 6C and 6D.

Ink. t. Patent- och reg.verket

+46 31630263

2002 -01- 2 1

Huvudfaxen Kassar

16

In Figure 6A the example of map information data 3 is presented at the lowest resolution level. Using the node, link and ring approach the information presented in Figure 6A will consist of the following structural aggregation.

- Node NB (point=<coordinate>)
- Link LAC (startNode=NB, endNode=NB, breakpoints=<coordinate>,...)
- Ring RAB (links=LAC)

These objects are completely defined in the low-resolution geodata including coordinates and reference each other.

15

In Figure 6B, the map information data 3 presented in Figure 6A is presented with a higher resolution level compared to the map information data 3 presented in Figure 6A. Using the function of link enhancement leads to a disaggregation of the map information presented in Figure 6A to the map information presented in Figure 6B.

LinkEnhance (link=LAC waveletParameters=<numbers>)

Thus the function link enhancement enhances the resolution of the link LAC. This is done by one step of the inverse wavelet transform (or similar to multi-resolution transform) using the old breakpoints as the low frequency parameters and the enclosed wavelet parameters as the high frequency component. This creates new breakpoints that closer describe the correct link.

In Figure 6C the map information data 3 presented in Figure 6B is presented with a higher resolution level

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfaxen Kassar

17

compared to the map information data 3 presented in Figure 6B. Using the function of link clipping, the link LAC is divided to two sub links, LA and LC. This also leads to the formation of the node NA.

5

Node NA (point=<coordinate>)

LinkClip (link=LAC afterBreakPoint=2 node=NA)

Thus, clip link LAC after the breakpoint and connect the new links (LA and LC) to the new node NA. Since the ring RAB referenced LAC was clipped, it must be updated to reference LA and LC instead.

In Figure 6D, the map information data 3 presented in Figure 6C is presented with a higher resolution level compared to the map information data 3 presented in Figure 6C. Using the function of ring splitting, the ring RAB of Figure 6C is divided into two sub rings, RA and RB.

20

Link LB (startNode=NA, endNode=NB, breakpoints=<coordinate>,...)

RingSplit (ring=RAB link=LB)

Thus, this splits ring RAB at the new link LB and creates the two new rings RA and RB. The example above could in the highest resolution for instance represent two areas of forest, one with broad-leaf trees and one with coniferous trees. At the lower resolution the two areas are aggregated and represent just forest. In Figures 6B to 6D, the intermediate resolution levels that are at least calculated, but not necessarily provided to the display unit, to receive the next resolution level.

Ink. t. Patent- och reg.verket

2002-01-21

Huvudfaxen Kassar

18

PATENT CLAIMS

1. Device (1) for providing map information data (3) interactively to a display unit (5) operated by a user;
-the device (1) comprising a processor (7) and a memory
5 (9) comprising a map information database (11);
-the map information database (11) comprising map information data (3) representing geographical features, the map information data (3) being based on aggregations of at least one of nodes (15), links (17) and rings (19),
10 each one of which corresponding to geographic features, offering a number of resolution levels, where
-the map information data (3) of a higher resolution level comprises additional map information data, resulting in more detailed map information (3) presented on the display unit
15 (5), compared to the map information data (3) of a lower resolution level, and
-the map information data (3) of a higher resolution level being generated by enhancement
20 of the map information data (3) of a lower resolution level combined with the additional data, the enhancement being based on disaggregation of at least one of the nodes (15), links (17) and rings (19);
25 the processor (7) being configured for:
-receiving from the user a request for map information data (3);
-providing to the display unit (5), in the case of the request being a first request, map information data (3)
30 at a predetermined resolution level and, in the case of the request being subsequent request, map information data (3) at a higher resolution level.

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassar

19

2. Device according to claim 1, wherein the predetermined resolution level corresponds to the lowest resolution level.

5 3. Device according to claim 1, wherein the processor (7) is further configured for, in the case of the request being subsequent request, providing map information data (3) at a lower resolution level.

10 4. Device according to claim 1, wherein, in the case of the request being subsequent request, the difference in resolution level between a presently provided map information data (3) and a previously provided map information data (3) is 1, or greater than 1.

15

5. Device according to claim 1, further comprising communication means (23) and wherein the memory (9) comprising the map information database (11) is remotely located and accessible using the communication means

20 (23).

6. Device according to claim 1, further comprising communication means (23) and wherein the database (11) is arranged in memories (7) at two locations, in which lower resolution levels are arranged in one memory (7) and higher resolution levels are arranged in the other memory (7).

25 7. Device according to claim 1, wherein the display unit 30 (5) is constituted by a computer screen.

Ink. 1. Patent- och reg.verket

+46 31630263

2002-01-21

Huvudfaxen Kassen

20

8. Device according to claim 1, further comprising communication means (23) between the device (1) and the display unit (5), and the display unit (5) being constituted by one of a cell phone, personal digital assistant (PDA), and a navigator.

9. A map information data carrier to be used in a device for providing map information data, comprising a map information database (11) comprising map information data (3) representing geographical features, the map information data (3) being based on aggregations of at least one of nodes (15), links (17) and rings (19), each one of which corresponding to geographic features, offering a number of resolution levels, where

15 -the map information data (3) of a higher resolution level comprises additional map information data (3), resulting in more detailed map information presented on the display unit (5), compared to the map information data (3) of a lower resolution level, and

20 -the map information data (3) of a higher resolution level being generated by enhancement of the map information data (3) of a lower resolution level combined with the additional data, the enhancement being based on disaggregation of at least one of the nodes (15), links

25 (17) and rings (19).

10. Device for providing map information data to a planning apparatus (33) for planning at least one of locations of society facility and travel routes;

30 -the device (31) comprising a processor (7) and a memory (9) comprising a map information database (11);

-the map information database (11) comprising map information data (3) representing geographical features,

Ink. t. Patent- och reg.verket

+46 31630263

2002-01-21

Huvudfaxen Kasse

21

the map information data (3) being based on aggregations of at least one of nodes (15), links (17) and rings (19), each one of which corresponding to geographic features, offering a number of resolution levels, where

- 5 -the map information data (3) of a higher resolution level comprises additional map information data, resulting in more detailed map information, compared to the map information data (3) of a lower resolution level, and
- 10 -the map information data (3) of a higher resolution level being generated by enhancement of the map information data (3) of a lower resolution level combined with the additional data, the enhancement being based on
- 15 disaggregation of at least one of the nodes (15), links (17) and rings (19);

the processor (7) being configured for:

- receiving from the user a request for map information data (3);
- 20 -providing to the planning apparatus (33), in the case of the request being a first request, map information data (3) at a predetermined resolution level and, in the case of the request being subsequent request, map information data (3) at a higher resolution level.

25

Ink. t. Patent- och reg.verket

+46 31630263

2002 -01- 2 1

Huvudfaxen Kasse

22

SUMMARY

Device (1) and carrier for providing map information data (3) interactively to a display unit (5). The device (1) comprises a processor (7) and a memory (9) comprising a map information database (11) comprising map information data (3) representing geographical features, the map information data (3) being based on aggregations of at least one of nodes (15), links (17) and rings (19), each one of which corresponding to geographic features. The map information data (3) of a higher resolution level comprises additional map information data, resulting in more detailed map information (3) presented on the display unit (5), compared to the map information data (3) of a lower resolution level. The map information data (3) of a higher resolution level is generated by enhancement of the map information data (3) of a lower resolution level combined with the additional data, the enhancement being based on disaggregation of nodes (15), links (17) and rings (19). The processor (7) is configured for receiving a request for map information data (3); and providing map information data (3). Also, a device for providing map information data to a planning apparatus (33) for planning at least one of locations of society facility and travel routes is disclosed.

25

(Fig. 1)



Ink. t. Patent- och reg.verket

+46 31630263

2002-01-21

Huvudfaxen Kassa

1/3



Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huyudfaxen Kassan

2/3




Fig. 3




Fig. 4




Fig. 5

Ink. t. Patent- och reg.verket

2002 -01- 2 1

Huvudfaxen Kassar

+46 31630263

3/3




Fig. 6a




Fig. 6b




Fig. 6c




Fig. 6d

02 01/21 14:15 FAX +46 31630263

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.